

|                                                    |                                                                                      |
|----------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>POLYCAB</b><br><small>IDEAS. CONNECTED.</small> | <b>POLYCAB INDIA LIMITED</b><br><b>LDC LP No. 07/2025-26 Dtd : 1st December 2025</b> |
| <b>List of Products Covered in Our LDC LP</b>      |                                                                                      |
| <b>Project Wires (200-300 Mtrs.)</b>               |                                                                                      |
| <b>Single Core Flexible Cables</b>                 |                                                                                      |
| <b>Multicore Flexible Cables</b>                   |                                                                                      |
| <b>Single Core XLPE Unarmoured/Armoured Cables</b> |                                                                                      |
| <b>Solar Cables</b>                                |                                                                                      |
| <b>BMS Cables</b>                                  |                                                                                      |
| <b>Braided Cables</b>                              |                                                                                      |
| <b>Steel Braided Cables</b>                        |                                                                                      |
| <b>Welding Cables</b>                              |                                                                                      |
| <b>Aluminium Service Wires</b>                     |                                                                                      |
| <b>Festoon Cables</b>                              |                                                                                      |
| <b>Uninyvin Cables</b>                             |                                                                                      |

**POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES  
FLAME RETARDANT LEAD FREE (FRLF) / FLAME RETARDANT LOW SMOKE (FRLSH) / HEAT  
RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-694:2010  
WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100  
VOLTS**

**POLYCAB PVC INSULATED SINGLE CORE  
UNSHEATHED INDUSTRIAL(MULTISTRAND)  
CABLES – HALOGEN FREE FLAME RETARDANT  
(HFFR) WITH BRIGHT ANNEALED ELECTROLYTIC  
BARE COPPER CONDUCTOR FOR VOLTAGE  
GRADE 1100 VOLTS**

| Size<br>(sq.mm.) | FRLF                                   | FRLS-H                                 | GREEN WIRES<br>HR-FRLS-H-LF            | HFFR                                   | Coils Per Box |
|------------------|----------------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|---------------|
|                  | 300 Mtrs (0.75-2.5)<br>200 Mtrs (4-16) | 300 Mtrs (0.75-2.5)<br>200 Mtrs (4-16) | 300 Mtrs (0.75-2.5)<br>200 Mtrs (4-16) | 300 Mtrs (0.75-2.5)<br>200 Mtrs (4-16) |               |
| 0.75             | 7120                                   | 7260                                   | 7480                                   | 7735                                   | 10            |
| 1                | 9205                                   | 9365                                   | 9625                                   | 9870                                   | 8             |
| 1.5              | 13455                                  | 13715                                  | 14050                                  | 14460                                  | 6             |
| 2.5              | 22290                                  | 22670                                  | 23310                                  | 23990                                  | 4             |
| 4                | 23175                                  | 23435                                  | 24220                                  | 24935                                  | 4             |
| 6                | 34190                                  | 34615                                  | 35750                                  | 36765                                  | 3             |
| 10               | 59025                                  | 59645                                  | 61655                                  | 63400                                  | 1             |
| 16               | 92875                                  | 93790                                  | 97010                                  | 99775                                  | 1             |

**Notes**

1. The above rates are exclusive of GST which shall be charged extra.
2. This Price List is subject to change without notice.
3. As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.

| POLYCARB                                                                                                                                                               |                                            |                                  |                     |         | POLYCARB INDIA LIMITED                                                                                                                                                                      |        |        |                    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|----------------------------------|---------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|--------|--------------------|
| IDEAS. CONNECTED.                                                                                                                                                      |                                            |                                  |                     |         | LDC LP No. 07/2025-26 Dtd : 1st December 2025                                                                                                                                               |        |        |                    |
| Polycab FR PVC Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts |                                            |                                  |                     |         | Polycab PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Flexible Cables for Voltage Grade 1100 Volts conforming to IS: 694:2010 |        |        |                    |
| Nominal Area of Conductor (sq mm)                                                                                                                                      | Number/ Nom. Dia of Conductor (No./dia mm) | Current Carrying Capacity (Amps) | (Price in Rs./100m) |         | (Price in Rs./100m)                                                                                                                                                                         |        |        |                    |
|                                                                                                                                                                        |                                            |                                  | Single Core         | Packing | 2 Core                                                                                                                                                                                      | 3 Core | 4 Core | 2 - 4 Core Packing |
| 0.5                                                                                                                                                                    | 16/.2                                      | 5                                | 1690                | 24      | 4240                                                                                                                                                                                        | 5820   | 7445   | 5                  |
| 0.75                                                                                                                                                                   | 24/.2                                      | 8                                | 2370                | 24      | 5675                                                                                                                                                                                        | 7875   | 10125  | 5                  |
| 1                                                                                                                                                                      | 32/.2                                      | 13                               | 2985                | 20      | 7215                                                                                                                                                                                        | 10010  | 12945  | 5                  |
| 1.5                                                                                                                                                                    | 30/.25                                     | 17                               | 4290                | 16      | 9840                                                                                                                                                                                        | 14145  | 18350  | 5                  |
| 2.5                                                                                                                                                                    | 50/.25                                     | 24                               | 7060                | 12      | 16300                                                                                                                                                                                       | 22300  | 30100  | 4                  |
| 4                                                                                                                                                                      | 56/.3                                      | 30                               | 10875               | 8       | 23900                                                                                                                                                                                       | 34300  | 45700  |                    |
| 6                                                                                                                                                                      | 84/.3                                      | 38                               | 16300               | 6       | 35200                                                                                                                                                                                       | 50600  | 67100  |                    |
| 10                                                                                                                                                                     | 80/.4                                      | 52                               | 28400               | 1       | 60100                                                                                                                                                                                       | 88400  | 116500 |                    |
| 16                                                                                                                                                                     | 126/.4                                     | 70                               |                     | 1       | 94800                                                                                                                                                                                       | 138700 | 183100 |                    |
| 25                                                                                                                                                                     | 196/.4                                     | 88                               |                     | 1       | 158100                                                                                                                                                                                      | 229900 | 300300 |                    |
| 35                                                                                                                                                                     | 276/.4                                     | 110                              |                     | 1       | 220200                                                                                                                                                                                      | 319600 | 420000 |                    |
| 50                                                                                                                                                                     | 396/.4                                     | 145                              |                     | 1       | 312200                                                                                                                                                                                      | 455200 | 601200 |                    |
| 70                                                                                                                                                                     | 354/.5                                     | 215                              |                     | 1       | 443800                                                                                                                                                                                      | 631400 | 834700 |                    |

**Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts**

| Nominal Area of Conductor (sq mm) | Number/ Nom. Dia of Conductor (No./dia mm) | Current Carrying Capacity (Amps) | (Price in Rs./100m) |         |
|-----------------------------------|--------------------------------------------|----------------------------------|---------------------|---------|
|                                   |                                            |                                  | Single Core         | Packing |
| 0.5                               | 16/.2                                      | 5                                | 1730                | 24      |
| 0.75                              | 24/.2                                      | 8                                | 2435                | 24      |
| 1                                 | 32/.2                                      | 13                               | 3020                | 20      |
| 1.5                               | 30/.25                                     | 17                               | 4325                | 16      |
| 2.5                               | 50/.25                                     | 24                               | 7160                | 12      |
| 4                                 | 56/.3                                      | 30                               | 11050               | 8       |
| 6                                 | 84/.3                                      | 38                               | 16500               | 6       |
| 10                                | 80/.4                                      | 52                               | 29000               | 1       |
| 16                                | 126/.4                                     | 70                               | 44900               | 1       |
| 25                                | 196/.4                                     | 88                               | 69800               | 1       |
| 35                                | 276/.4                                     | 110                              | 97700               | 1       |
| 50                                | 396/.4                                     | 145                              | 139300              | 1       |
| 70                                | 354/.5                                     | 215                              | 196900              | 1       |
| 95                                | 484/.5                                     | 260                              | 259600              | 1       |
| 120                               | 608/.5                                     | 305                              | 341400              | 1       |
| 150                               | 750/.5                                     | 355                              | 427300              | 1       |
| 185                               | 925/.5                                     | 415                              | 541800              | 1       |
| 240                               | 1210/.5                                    | 500                              | 693900              | 1       |
| 300                               | 1527/.5                                    | 585                              | 868300              | 1       |
| 400                               | 2036/.5                                    | 695                              | 1157000             | 1       |
| 500                               |                                            |                                  | 1447400             | 1       |
| 630                               |                                            |                                  | 1866700             | 1       |

**Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Flexible Cables for Voltage Grade 1100 Volts conforming to IS: 694:2010**

| (Price in Rs./100m) |         |         |                    |         |        |
|---------------------|---------|---------|--------------------|---------|--------|
| 2 Core              | 3 Core  | 4 Core  | 2 - 4 Core Packing | 5 Core  | 6 Core |
| 4510                | 6080    | 7705    | 5                  | 9680    | 11600  |
| 6015                | 8195    | 10450   | 5                  | 13700   | 16600  |
| 7535                | 10380   | 13300   | 5                  | 17650   | 21225  |
| 10250               | 14600   | 18700   | 5                  | 24100   | 29300  |
| 16800               | 23000   | 30900   | 4                  | 39200   | 47400  |
| 24500               | 35200   | 46400   |                    | 62100   | 74300  |
| 36100               | 51500   | 68100   |                    | 91300   | 109800 |
| 61100               | 89700   | 118500  |                    | 157600  |        |
| 97400               | 141900  | 186600  |                    | 242200  |        |
| 161400              | 234500  | 306700  |                    | 439600  |        |
| 224600              | 325800  | 429100  |                    | 602700  |        |
| 318900              | 464100  | 612700  |                    | 872500  |        |
| 452500              | 643900  | 851400  |                    | 1193200 |        |
|                     | 912700  | 1204000 |                    |         |        |
|                     | 1158900 | 1529500 |                    |         |        |
|                     | 1448700 | 1912200 |                    |         |        |
|                     | 1784000 | 2358100 |                    |         |        |
|                     | 2303100 | 3048600 |                    |         |        |
|                     | 2873800 | 3805600 |                    |         |        |
|                     | 3829100 | 5040600 |                    |         |        |
|                     |         |         |                    |         |        |
|                     |         |         |                    |         |        |

**Polycab PVC Insulated, FRLS Round Sheathed Multi Core Industrial Flexible Cables conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts**

| Nominal Area of Conductor (sq mm) | Number/ Nom. Dia of Conductor (No./dia mm) | Current Carrying Capacity (Amps) | Price in Rs./100 Mtrs. |         |         |         |
|-----------------------------------|--------------------------------------------|----------------------------------|------------------------|---------|---------|---------|
|                                   |                                            |                                  | 7 Core                 | 8 Core  | 10 Core | 12 Core |
| 0.5                               | 16/.2                                      | 5                                | 13000                  | 15400   | 19200   | 22400   |
| 0.75                              | 24/.2                                      | 8                                | 18600                  | 21700   | 27300   | 31800   |
| 1                                 | 32/.2                                      | 13                               | 24000                  | 27900   | 34500   | 41200   |
| 1.5                               | 30/.25                                     | 17                               | 32900                  | 38100   | 48600   | 57200   |
| 2.5                               | 50/.25                                     | 24                               | 54300                  | 64500   | 79200   | 95100   |
| 4                                 | 56/.3                                      | 30                               | 89700                  |         |         |         |
|                                   |                                            |                                  |                        |         |         |         |
| Nominal Area of Conductor (sq mm) | Number/ Nom. Dia of Conductor (No./dia mm) | Current Carrying Capacity (Amps) | Price in Rs./100 Mtrs. |         |         |         |
|                                   |                                            |                                  | 14 Core                | 16 Core | 19 Core | 24 Core |
| 0.5                               | 16/.2                                      | 5                                | 25800                  | 29400   | 34000   | 42900   |
| 0.75                              | 24/.2                                      | 8                                | 37300                  | 42000   | 49600   | 62000   |
| 1                                 | 32/.2                                      | 13                               | 47800                  | 54400   | 64000   | 80100   |
| 1.5                               | 30/.25                                     | 17                               | 67500                  | 77900   | 90500   | 115900  |
| 2.5                               | 50/.25                                     | 24                               | 110500                 | 126300  | 146300  | 189500  |

**Polycab Multi Strand Bare Copper conductor XLPE insulated PVC Sheathed Cables**

| Nominal Area    | No/Dia of Strands | Current rating in Air at 40°C | Cu Conductor Unarmoured Cables | Cu Conductor Aluminium Armouring Cables |
|-----------------|-------------------|-------------------------------|--------------------------------|-----------------------------------------|
| mm <sup>2</sup> | No/mm             |                               | Rs/100 Mtr.                    | Rs/100 Mtr.                             |
| 6               | 84/0.3            | 55                            | 21900                          | 29800                                   |
| 10              | 80/0.4            | 75                            | 37000                          | 50300                                   |
| 16              | 126/0.4           | 103                           | 54500                          | 63900                                   |
| 25              | 196/0.4           | 126                           | 87000                          | 97400                                   |
| 35              | 276/0.4           | 152                           | 119500                         | 131400                                  |
| 50              | 396/0.4           | 189                           | 167000                         | 182800                                  |
| 70              | 354/0.5           | 240                           | 229200                         | 251600                                  |
| 95              | 484/0.5           | 297                           | 311500                         | 324400                                  |
| 120             | 608/0.5           | 346                           | 393900                         | 409900                                  |
| 150             | 750/0.5           | 390                           | 491800                         | 512300                                  |
| 185             | 925/0.5           | 460                           | 600700                         | 618400                                  |
| 240             | 1210/0.5          | 552                           | 780500                         | 814700                                  |
| 300             | 1527/0.5          | 640                           | 973000                         | 1024100                                 |
| 400             | 2036/0.5          | 753                           | 1297900                        | 1358200                                 |

**POLYCAB SOLAR CABLES**

|                                                                                                                                              |                       |  |                                                                                                                                                                                                          |                       |
|----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|--|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| Flexible Tinned Copper Conductor/ Cross linkable (E Beam) LSZH Insulation/ Cross linkable (E Beam) LSZH Sheathed Solar Cable as per EN 50618 |                       |  | Flexible Tinned Copper Conductor Single Core Multistrand, Cross Linked, Zero Halogen Low Smoke Insulation and Cross Linked Low Smoke Sheathing , Heat Resistant upto 120°C and UV Resistant Solar Cables |                       |
| Size in Sq.mm.                                                                                                                               | Price in Rs./100 Mtr. |  | Size in Sq.mm.                                                                                                                                                                                           | Price in Rs./100 Mtr. |
| 2.5                                                                                                                                          | 9350                  |  | 2.5                                                                                                                                                                                                      | 8800                  |
| 4                                                                                                                                            | 13500                 |  | 4                                                                                                                                                                                                        | 12700                 |
| 6                                                                                                                                            | 19700                 |  | 6                                                                                                                                                                                                        | 18800                 |
| 10                                                                                                                                           | 33900                 |  |                                                                                                                                                                                                          |                       |
| 16                                                                                                                                           | 54700                 |  |                                                                                                                                                                                                          |                       |
| 25                                                                                                                                           | 86900                 |  |                                                                                                                                                                                                          |                       |

**POLYCAB BUILDING MANAGEMENT SYSTEM CABLE (BMS)**

Flexible Bare Copper Conductor, PVC Insulated,Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Price in Rs./100m)

| Cores | 0.5 sq.mm | 0.75 sq.mm | 1.0 sq.mm | 1.5 sq.mm | 2.5 sq.mm |  |
|-------|-----------|------------|-----------|-----------|-----------|--|
| 2     | 7020      | 8990       | 10800     | 14125     | 22000     |  |
| 3     | 8710      | 11900      | 14300     | 19100     | 30500     |  |
| 4     | 10800     | 14400      | 18300     | 25600     | 38400     |  |
| 5     | 13300     | 17800      | 21700     | 29500     | 48500     |  |
| 6     | 15300     | 20200      | 25300     | 35700     | 58000     |  |
| 7     | 16700     | 23700      | 29300     | 40200     | 68700     |  |
| 8     | 19000     | 25600      | 32700     | 44900     | 76800     |  |
| 10    | 22600     | 31700      | 40200     | 55500     | 93800     |  |
| 12    | 26700     | 37100      | 47500     | 65800     | 115200    |  |
| 14    | 31100     | 43500      | 54900     | 75700     |           |  |
| 16    | 35000     | 48800      | 61800     | 87600     |           |  |
| 19    | 40200     | 58000      | 73000     | 101600    |           |  |
| 24    | 49800     | 71300      | 90200     | 129900    |           |  |

Packing - 100/300 Mtrs. Coils & 2000 Mtrs. Drums

Note : 4% Extra Charges for Drum Packing

**POLYCAB INDUSTRIAL BRAIDED CABLES**

**Polycab Annealed Bare Cu Flexible Conductor PVC Insulated, Tinned Cu Braided (Screened) PVC Sheathed Flexible Unarmoured Cables 1100 Volts. (Price in Rs./100 Mtr)**

| Cores | 0.5 Sq mm. | 0.75 Sq mm. | 1.0 Sq mm. | 1.5 Sq mm. | 2.5 Sq mm. | 4 Sq mm. | 6 Sq mm. | 10 Sq mm. | 16 Sq mm. | 25 Sq mm. | 35 Sq mm. |
|-------|------------|-------------|------------|------------|------------|----------|----------|-----------|-----------|-----------|-----------|
| 2     | 12300      | 15000       | 17000      | 20600      | 31100      | 46200    | 59900    |           |           |           |           |
| 3     | 14300      | 18700       | 23000      | 28400      | 41600      | 65500    | 91600    | 146200    | 209900    | 395200    | 518900    |
| 4     | 17700      | 23000       | 27900      | 34800      | 52500      | 80000    | 111400   | 186700    | 301100    | 476500    | 659800    |
| 5     | 22400      | 27500       | 32100      | 42200      | 70600      |          |          |           |           |           |           |
| 6     | 23700      | 32100       | 36600      | 49500      | 79200      |          |          |           |           |           |           |
| 7     | 25500      | 35800       | 41600      | 54800      | 89400      |          |          |           |           |           |           |
| 8     | 29700      | 42600       | 47300      | 63200      | 93300      |          |          |           |           |           |           |
| 10    | 37700      | 47100       | 62900      | 79400      | 104300     |          |          |           |           |           |           |
| 12    | 42600      | 53100       | 67500      | 89400      | 122100     |          |          |           |           |           |           |
| 14    | 47100      | 62900       | 79200      | 107100     | 146800     |          |          |           |           |           |           |
| 16    | 50400      | 73200       | 88900      | 118200     | 172800     |          |          |           |           |           |           |
| 19    | 59900      | 86800       | 104900     | 146800     | 223100     |          |          |           |           |           |           |
| 24    | 72400      | 96900       | 131500     | 179800     | 279600     |          |          |           |           |           |           |

**POLYCAB MULTICORE STEEL BRAIDED CABLES**

**Flex Bare Copper Conductor,PVC Insulated, Cores Laid Up Together PVC Inner Sheathed, GI Wire Braided (Flexible Armouring), Overall PVC Sheathed Steel Braided Cables. (Price in Rs./100 Mtr.)**

| Cores | 0.5 Sq.mm. | 0.75 sq.mm | 1.0 sq.mm | 1.5 sq.mm | 2.5 sq.mm | 4 sq.mm | 6 sq mm |
|-------|------------|------------|-----------|-----------|-----------|---------|---------|
| 2     | 13300      | 16200      | 18000     | 22500     | 32200     | 45400   | 63200   |
| 3     | 16300      | 19700      | 22700     | 29100     | 43400     | 64300   | 88200   |
| 4     | 19200      | 24100      | 28100     | 36500     | 55000     | 80100   | 114700  |
| 5     | 22500      | 28600      | 34300     | 44500     | 66500     |         |         |
| 6     | 25500      | 33200      | 39600     | 51600     | 78500     |         |         |
| 7     | 27600      | 36400      | 43600     | 57800     | 88200     |         |         |
| 8     | 31400      | 41100      | 49100     | 66300     | 101500    |         |         |
| 10    | 38400      | 50500      | 60700     | 81200     | 125700    |         |         |
| 12    | 43700      | 58600      | 70100     | 94600     | 146900    |         |         |
| 14    | 49600      | 66500      | 80100     | 109000    | 169100    |         |         |
| 16    | 55800      | 74900      | 90800     | 122900    | 192300    |         |         |
| 19    | 64000      | 86800      | 106200    | 144100    | 225200    |         |         |
| 24    | 80000      | 108500     | 132900    | 180900    | 282700    |         |         |

| Cores | 10 Sq.mm. | 16 Sq.mm. | 25 Sq.mm. | 35 Sq.mm. | 50 Sq.mm. | 70 Sq.mm | 95 Sq.mm. |
|-------|-----------|-----------|-----------|-----------|-----------|----------|-----------|
| 2     | 103500    | 154800    | 234600    | 319900    | 454400    | 623500   | 833500    |
| 3     | 145700    | 219000    | 336700    | 460700    | 655300    | 904900   | 1210900   |
| 4     | 190000    | 287500    | 443200    | 607900    | 864000    | 1194200  | 1600200   |

**Note : 3% Extra Charges for Drum Packing**

| <b>POLYCAB INDUSTRIAL COPPER WELDING CABLES</b>                   |                           |                                      |                                 |
|-------------------------------------------------------------------|---------------------------|--------------------------------------|---------------------------------|
| <b>Polycab Flexible Copper Conductor 1100 Volts Welding Cable</b> |                           |                                      |                                 |
| Nominal Area of Conductor (sq mm)                                 | Current Carrying Capacity | Conductor Constn. Strands/ Dia in mm | HOFR Insulation Price/100m (Rs) |
| 16                                                                | 120                       | 509/0.2                              | 53200                           |
| 25                                                                | 160                       | 796/0.2                              | 83200                           |
| 35                                                                | 230                       | 1115/0.2                             | 114900                          |
| 50                                                                | 400                       | 703/0.3                              | 163100                          |
| 70                                                                | 600                       | 999/0.3                              | 230700                          |
| 95                                                                | 700                       | 1346/0.3                             | 303800                          |
| 120                                                               | 1100                      | 1699/0.3                             | 388700                          |

**POLYCAB ALUMINIUM WIRES & CABLES**

**POLYCAB SINGLE CORE PVC INSULATED 1100 VOLTS  
SOLID ALUMINIUM CONDUCTOR WIRES AS PER IS  
694**

| Size in Sq.mm. | Price in Rs./100 Mtr. |
|----------------|-----------------------|
| 1.5            | 1620                  |
| 2.5            | 2560                  |
| 4              | 3630                  |
| 6              | 4970                  |
| 10             | 8325                  |
| 16             | 12100                 |
| 25             | 18700                 |
| 35             | 25600                 |
| 50             | 29100                 |
| 70             | 38200                 |
| 95             | 67800                 |
|                |                       |
|                |                       |
|                |                       |
|                |                       |

**POLYCAB PVC INSULATED AND SHEATHED TWIN CORE FLAT & THREE  
CORE ROUND CABLES 1100 VOLTS EACH CORE HAVING SINGLE SOLID  
ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694**

| No. of Cores | Sq.mm. | Price in Rs./100 Mtr. |
|--------------|--------|-----------------------|
| 2 Core       | 2.5    | 8850                  |
| 2 Core       | 4      | 11900                 |
| 2 Core       | 6      | 15700                 |
| 2 Core       | 10     | 22800                 |
| 2 Core       | 16     | 33200                 |
| 3 Core       | 2.5    | 13000                 |
| 3 Core       | 4      | 17200                 |
| 3 Core       | 6      | 20000                 |
| 3 Core       | 10     | 37100                 |
| 3 Core       | 16     | 49500                 |
| 4 Core       | 2.5    | 15900                 |
| 4 Core       | 4      | 22300                 |
| 4 Core       | 6      | 31600                 |
| 4 Core       | 10     | 46600                 |
| 4 Core       | 16     | 61800                 |

**FESTOON CABLES**

(Price in Rs./Mtr.)

| Cores | 0.5 Sq.mm. | 0.75 Sq.mm. | 1 Sq.mm. | 1.5 Sq.mm. | 2.5 Sq.mm. | 4 Sq.mm. |
|-------|------------|-------------|----------|------------|------------|----------|
| 3     | 97         | 120         | 151      | 199        | 327        | 499      |
| 4     | 126        | 164         | 198      | 271        | 428        | 670      |
| 5     | 178        | 232         | 293      | 376        | 598        | 895      |
| 6     | 211        | 283         | 350      | 446        | 718        | 1082     |
| 7     | 240        | 318         | 403      | 516        | 836        | 1255     |
| 8     | 280        | 366         | 456      | 596        | 962        | 1438     |
| 9     | 324        | 428         | 535      | 682        | 1107       | 1640     |
| 10    | 357        | 472         | 589      | 757        | 1223       | 1831     |
| 12    | 420        | 561         | 702      | 896        | 1460       | 2186     |
| 14    | 507        | 661         | 824      | 1068       | 1716       | 2563     |
| 16    | 571        | 756         | 951      | 1213       | 1963       | 2935     |
| 18    | 635        | 831         | 1065     | 1361       | 2182       | 3262     |
| 24    | 862        | 1130        | 1442     | 1652       | 2937       | 4414     |

**UNINYVIN CABLES**

**Multistranded Annealed Tinned Copper Conductor 105° C PVC Insulation with Nylon Braiding with Lacquer Coating Uninyvin Cables**

| Cable Size | Nom. Conductor Area (Sq.mm.) | Price in Rs./Mtr. |
|------------|------------------------------|-------------------|
| 22         | 0.347                        | 34.50             |
| 20         | 0.556                        | 44.30             |
| 18         | 0.966                        | 65.30             |
| 16         | 1.17                         | 77.80             |
| 14         | 2.05                         | 120.00            |
| 12         | 3.22                         | 172.00            |
| 10         | 5.33                         | 245.00            |
| 8          | 8.76                         | 381.00            |
| 6          | 13.30                        | 564.00            |
| 4          | 21.50                        | 893.00            |
| 2          | 33.30                        | 1365.00           |
| 1          | 40.70                        | 1653.00           |
| 0          | 53.00                        | 2147.00           |
| 00         | 68.30                        | 2734.00           |
| 000        | 84.20                        | 3387.00           |
| 0000       | 109                          | 4356.00           |